

## MATERIAL SAFETY DATA SHEET

The information contained within this MSDS details health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user of this product should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Gripset Industries Pty Ltd. Gripset Industries Pty Ltd makes no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely, and to comply with all relevant Federal, State and Local Government laws and regulations. Gripset Industries Pty Ltd shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendation or information contained herein, from abnormal use of the material, or any hazard inherent in the nature of the material.

### STATEMENT OF HAZARDOUS NATURE

**Not classified as hazardous according to criteria of Worksafe Australia.**

### COMPANY DETAILS

Company	: Gripset Industries Pty Ltd A.C.N. 137 930 093
Address	: 30-32 Park Avenue, Woodville North SA 5012, Australia
Telephone numbers	: +61 (8) 8124-7300 or 1800 650 435
Facsimile number	: +61 (8) 8124-7350

### IDENTIFICATION

Product Name	: <b>Gripset B26</b>
Other Names	: None
Manufacturer's Product Code	: GS B26
UN Number	: None assigned
Dangerous Goods Class	: None assigned
Subsidiary Risk	: None assigned
Shipping Name	: None assigned
Hazchem Code	: None assigned
Poisons Schedule Number	: None assigned

### Use

Major recommended uses	: Asphalt crack sealing and protective coating applications
------------------------	---

### Physical Description / Properties

Appearance	: Black viscous paste
Boiling Point (°C)	: 100°C approx. (water)
Vapour Pressure	: As for water
Specific Gravity	: 1kg/Litre
Flashpoint (°C)	: Not Applicable
Flammability Limits	: Not Applicable
Solubility in Water	: Dilutable

### Other Properties

Auto Ignition Temperature	: Not Applicable
Vapour Density	: (Air = 1) < 1 water
Form	: Liquid
Stability	: Stable
Hazardous Polymerisation	: Will not occur
Materials to avoid	: Solvents, strong oxidizers, strong acids & alkalis.

### Ingredients

Chemical Name:	CAS Number:	Proportion:
Polymer	-	10 – 25%
Bitumen emulsion	64742-93-4	50 – 60%

\* Non hazardous ingredients are exempted according to NOHSC and SUSDP standards.

# MATERIAL SAFETY DATA SHEET

## HEALTH HAZARD INFORMATION

### Health Effects

#### Acute:

Swallowed	: No data supplied; but polymer is not expected to be harmful.
Eye	: May be an eye irritant
Skin	: Prolonged or repeated contact with skin may result in slight skin irritation.
Inhaled	: Excessive exposure to vapours or spray mist may cause slight irritation to eyes, nose and throat.

#### Chronic:

Swallowed	: No data supplied; but polymer is not expected to be harmful.
Eye	: Prolonged exposure may be an eye irritant
Skin	: Prolonged exposure may result in slight skin irritation.
Inhaled	: Prolonged exposure to vapours or spray mist may cause slight irritation to eyes, nose and throat.

### First Aid

Swallowed	: Give plenty of water. Seek medical assistance. Decision on induction of vomiting to be made by qualified person.
Eye	: Immediately flush with large amounts of water for at 5-10 minutes; lifting upper and lower lids. Seek medical attention if irritation persists.
Skin	: Wash with water and soap. Seek medical attention if irritation persists.
Inhaled	: If affected, move subject to fresh air. Seek medical assistance if symptoms persist.
First Aid Facilities	: Ensure availability of eye wash fountains and/or water access.
Advice to Doctor	: Treat symptomatically.

## PRECAUTIONS FOR USE

### Exposure Standards

Name:	STL:		TWA:	
	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm
Bitumen emulsion	-	-	0.5	-

\* Other Exposure information: Exposure standards not established for product, or other ingredients.

### Engineering Controls

Engineering Controls	: General ventilation is recommended during normal use. Local ventilation may be required during certain operations to prevent inhalation of vapours.
----------------------	---

### Personal Protection

Respirator Type (AS/NZS 1716)	: Where concentrations in air may exceed the recommended exposure limits, or work practice or other means of exposure reduction are not adequate, approved respirator may be necessary to prevent overexposure by inhalation.
Glove Type	: Neoprene/rubber gloves.
Eye Protection	: Chemical worker's goggles.
Clothing	: Protective clothing to cover body parts, e.g. long sleeved overalls or similar; and boots.
Other	: Wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.

### Flammability

Fire Hazards	: Product is non flammable according to the Australian Code for the Transport of Dangerous Goods; however dried film will burn in a general fire.
--------------	---

## MATERIAL SAFETY DATA SHEET

### SAFE HANDLING INFORMATION

#### Storage & Transport

Location	: Store in a cool area to prolong storage life.
Temperature Conditions	: Best stored at room temperature; Prevent from freezing.
Protection from Weather	: Store undercover and away from heat sources and electric plant.
Storage Incompatibilities	: Not applicable.

#### Spills & Disposal

Clean Up Spills / Leaks	: <i>Small spills:</i> Wipe up and wash area with water. <i>Large spills:</i> Dike and contain spill with sand or earth.  Do not contaminate streams, rivers, or water courses. Do not flush down drains and sewers. Inform local authority if liquid enters drains, sewers, streams, etc. Clean up before the material dries. Absorb the liquid with sand, earth or other absorbent. Place used absorbent in suitable, sealable labelled containers.
State / Territory Authority	: Observe all Federal, State and Local regulations.
Precautions for Clean Up Crew	: Nitrile rubber or PVC gloves.

#### Fire / Explosion Hazard

Hazard of Use / Storage	: Product will not support combustion. Polymer will burn in a general fire, once all the water has been driven off.
List of Dangerous Decomposition or Combustion Products	: Carbon monoxide, carbon dioxide, oxides of nitrogen, fumes and smoke.
Types of Extinguisher	: Water, Foam, CO <sub>2</sub> and Dry Chemical.
Precautions	: Fire fighters should wear self-contained breathing apparatus.
Protective Clothing	: None
Reactivity	: None

### OTHER INFORMATION

Ecology	: Avoid contaminating waterways and sewers.
Packaging & Labelling	: In 15 litre pails, 200 litre drums, 1000 litre IBC or bulk

### CONTACT POINT

Gripset Technical Department	: +61 (8) 8124-7300 or 1800 650 435
Australia Poisons Information Centre	: 13 11 26
Police & Fire Brigade:	: 000