



MULTIGRIP

Fire Retardant Primer for Membranes and Adhesives for Expanded Polystyrene Insulation

DESCRIPTION & USE

- Multigrip is a quick-setting synthetic elastomeric based liquid that forms a fireproof film when it dries
- Use to glue expanded polystyrene panels together.
- Use to glue gypsum boards, vapor barriers or the insulation to wood or steel flooring
- Use as primer for self-adhesive membranes

FEATURES & BENEFITS

- Excellent primer for self-adhesive membranes
- Compatible with expanded polystyrene
- Has a very liquid consistency which allows application with a sprayer
- Quick drying

TECHNICAL DATA

LEXCOR MULTIGRIP	
Format	5 gal (18.93 L)
Approximate weight	32 lbs
Colour	Red
Solids content	± 40%
Coverage as an adhesive	
Solid surface	200 ft ² /gal (± 8 m ² /L)
Corrugated steel support	300 ft ² /gal (± 9 m ² /L)
Drying time with 50% H.R.	20°C (68°F)
Initial set	30 minutes
Completely set	2 hours
Application temperature	-10°C to 35°C (14°F to 95°F)
Operating temperature	-40°C to 70°C (-54°F to 158°F)
System's susceptibility to fire	
Damp	Very flammable
Dry	Fireproof
Storage life-time	12 months
VOC	459 g/L < Water and free of solvent



APPLICATION

- The surface must be firm and free of particles, cracks, grease, oil and other substances. Must be free of frost, snow and ice.
- Mix adequately.
- Apply a bead in order to obtain maximum adhesion between two panels or expanded polystyrene insulation.

RESTRICTIONS

- Do not store in direct sunlight.
- Keep all unused containers closed.
- Contains extremely flammable solvents.
- Do not smoke or do any welding on the worksite.
- Avoid heat and open flames.
- Use in well ventilated areas.
- Avoid all contact with skin and avoid inhaling fumes for any lengthy period of time.
- Harmful if ingested.

lexcor.net

Visit our video channels: <https://vimeo.com/channels/lexcore>

COMMERCIAL BUILDING PRODUCTS

Ontario & Western Canada
1.800.268.2889



Quebec & Eastern Canada
1.800.363.2307